

MINNESOTA DEPARTMENT OF TRANSPORTATION MONUMENTATION PLAT NO. 31-M2

STATE PROJECT NO. 3109(46=165-22)
IN THE WEST HALF OF SECTION 17, T.148 N., R.27 W.
ITASCA COUNTY, MINNESOTA

THE COMMISSIONER OF TRANSPORTATION IS HEREBY DESIGNATING THE DEFINITE
LOCATION OF TRUNK HIGHWAY NO. 46 FROM 1.0 MILE SOUTH TO
0.75 MILE NORTH OF THE POPPLE RIVER

This is hereby certified as the official plat and Commissioner's Order
therefor for said T.H. 46 within the designated portion of said
Section 17 pursuant to Minnesota Statutes 160.14 and 161.16

Commissioner's Order No. 66604 Location PLATS 31-M1 AND 31-M2
Recommended for Certification: Certified:


Richard P. Brown
Commissioner of Transportation
Date 5-10-82
by F.L. Marshall
Assistant Commissioner of Transportation
Date 5-10-82

I hereby certify that this plat was prepared by me or under my direct supervision and that I am a duly
Registered Land Surveyor under the Laws of the State of Minnesota; that this plat meets requirements
of Minnesota Statutes, sections 160.16, Subd. 2 and section 161.16.

Certified by John E. Jensen 10460 5-7-82
Registered Land Surveyor Reg. No. Date
Office of Surveying & Mapping

I hereby certify that this plat was surveyed by me or under my direct supervision and that I am a duly
Registered Land Surveyor under the Laws of the State of Minnesota; that all measurements are correctly
shown on this plat and that all monuments have been correctly placed as shown on this plat.

Certified by Wallace B. Schubert 11866 8/11/82
Registered Land Surveyor Reg. No. Date
MNDOT District Office



CONVENTIONAL SYMBOLS

Section Line	Access Control
Quarter Line	Access Opening
Sixteenth Line	Cast Iron Monument or 2x2 D.D.T. Iron Pipe with
Property Line	Aluminum Cap
R/W Boundary	3/4" D.D.T. Iron Pin
Other Road R/W's	Other Iron Monument
Railroad R/W	Concrete or Stone Monument
Private Easement	R/W Boundary Corner

DISTANCES SHOWN TO FEET 66.66 ETC ARE EXTRINSIC VALUES.

SURVEY STANDARDS

1. The plat values, azimuths and distances, are based on the project control survey system.
2. The boundary monuments shown on this plat have been field checked for location. The standard deviation for the monument position is 0.1 ft.
3. Certificates of Location have been filed at the County Recorder's Office and/or the County Surveyor's Office for the section corner monuments shown on this plat.
4. For details of this survey contact the Surveying and Mapping Section at the Minnesota Department of Transportation, BEMIDJII, Name of District

AZIMUTH ORIENTATION
Plat azimuths are oriented to an assumed
coordinate system with the North Line of Section 28
being 89° 22' 44"

